



Cambridge Part #	Length (L)	Width (W)	Thickness (T)	Max Bundle Dia.
CT17-175	16.93 [430]	0.35 [9.0]	0.08 [2.03]	4.33 [110]
CT21-175	20.71 [526]	0.35 [9.0]	0.08 [2.03]	5.51 [140]
CT24-175	24.02 [610]	0.35 [9.0]	0.08 [2.03]	7.00 [187]
CT32-175	32.09 [815]	0.35 [9.0]	0.08 [2.03]	9.41 [239]
CT36-175	35.91 [912]	0.35 [9.0]	0.08 [2.03]	10.35 [263]
CT48-175	48.00 [1220]	0.35 [9.0]	0.08 [2.03]	14.37 [365]
CT60-175	60.23 [1530]	0.35 [9.0]	0.08 [2.03]	18.15 [460]

*Please Inquire About Other Sizes Not Listed
 **See Cambridge Catalog for Colors and Packaging Options



PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CODA RESOURCES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CODA RESOURCES IS PROHIBITED.

Rated Operating Temperatures:
 -40°F to 185°F (-40°C to 85°C)

Usage Recommendations:
 The cable ties must be stored at room temperature in at least 50% humidity (recommended 80%RH) in a completely sealed polyethylene bag if not being used. In extreme heat and cold, limit the exposure of unused cable ties. If after being exposed to extreme temperatures and/or extreme relative humidities, the cable ties must be allowed to be stored at room temperature and at least 50% humidity (recommended 80%RH) for at least 24 hrs in a sealed bag before being used again

	NAME	DATE	CAMBRIDGE 960 Alabama Ave, Brooklyn, NY 11207 P:718-649-1666 F:718-485-4403		
DRAWN	J Li	10/17/06			
UNLESS OTHERWISE SPECIFIED:			TITLE: Cambridge Cable Ties 175lb Tensile Strength		
DIMENSIONS ARE IN INCHES [] DENOTES MILLIMETER			SIZE	DWG. NO.	REV
MATERIAL Nylon 6,6 94V-2			A	CT-175 REV A	A
FINISH			DO NOT SCALE DRAWING		
			SCALE: 1:1	WEIGHT:	SHEET 1 OF 1