

## Magnetic Hex and Hollow Nut

Specifications on Page 117

## Handles and Drivers

Sold together, each package includes both the Handle & Chuck Driver. The Connext difference is a quick-connect holder mechanism that accepts any 1/4-inch shank chuck driver to any handle.

#### Magnetic Hex Hand Drivers with CONNEXT1 standard & CONNEXT2 stubby handles

Precision-fit and hardened Malco Magnetic Hex Chuck Driver shaft components, offer the ultimate in Hex Hand Driver durability and flexibility. Insert shanks are available in 2-inch, 3-inch and Big 7-inch lengths.



#### Hollow Nut Drivers with CONNEXT1 standard handle

Hollow Hex Chuck Drivers with 1/4-inch power insert shanks are available in 3-inch and big 7-inch lengths. All Malco Hex Chuck drivers are now COLOR CODED for easy size identification whether installed on a power drill or used with a CONNEXT™ Handle.

#### Size Recognition Color Key

- Red 1/4" Hex Opening
- Yellow 5/16" Hex Opening
- Blue 3/8" Hex Opening





## Ratcheting Handle

## and Professional Kits

## An impressive array of CONNEXT™ drive shaft combinations now includes Kits and a versatile Ratcheting Handle.

A forward or reverse ratchet driving mechanism, as well as the locked driving position of the New CONNEXT Ratcheting Handle, meets torque capacity standards (including ANSI) comparable to a 1/2-inch solid shaft driver! The clear, molded acetate, full grip is shock-proof, shatter-proof and fluted to fit any hand. And a quick-connect holder mechanism accepts any 1/4-inch hex shank power drive or insert bit as a shaft including all Malco hollow, or magnetic hex chuck drivers.

Full, Stubby &

Ratcheting

style grips, plus all Handles feature a

quick-connect holder and are color

coded for easy size recognition!



#### Magnetic Hex Driver & Nut Driver Kits

Whole Kits of possibilities feature popular assortments of handles and hollow or magnetic hex chuck driver shafts in a tough Cordura Pouch with belt clip and Velcro closure.

# CONNEXT4 Kit Magnette

## 9 Piece MagneticHex Hand Driver Kit

Popular assortment of Malco CONNEXT Handles and Magnetic Hex Chuck Driver Shafts. Contents includes: 2-each 1/4-in. and 5/16-in. driver shafts in short, medium and long varieties and 3 handles, including stubby, full grip and full grip ratcheting style.



#### 12 Piece Magnetic Hex Hand Driver Kit

Deluxe assortment of Malco CONNEXT Handles and Magnetic Hex Chuck Driver Shafts. Contents includes: 3-each 1/4-in., 5/16-in. and 3/8-in. driver shafts in short, medium and long varieties and 3 handles, including stubby, full grip and full grip ratcheting style.



#### 8 Piece Nut Driver Kit

Popular assortment of Malco CONNEXT Handles and Hollow Hex Chuck Driver Shafts. Contents includes: 2-each 1/4-in., 5/16-in. and 3/8-in. driver shafts in short and long varieties and 2 handles including a full grip ratcheting style and a full grip.





## Drivers, Handles and Accessories

#### Robertson® Style Square Head Chuck Drivers

- Fully hardened, power-groove style driver.
- Square tip will not cam out.

• #1 and #2 drivers available in 1-3/4 in. and 2-1/2 in. lengths.







Catalog Number	Description	Point Size	Color	Shank Dia. in.	Overall Length in. (mm)
SD1	Square Head Driver	#1		1/4	1-3/4 (45)
SD2	Square Head Driver	#2	•	1/4	1-3/4 (45)
SDX1	Square Head Driver	#1		1/4	2-1/2 (63)
SDX2	Square Head Driver	#2	•	1/4	2-1/2 (63)









Magnetic Hex Drivers 1/4 and 5/16 sizes also available in bulk tubs of 100.

#### Magnetic Hex Drivers Long Style 1/4 and 5/16 sizes also

available in bulk tubs of 50.







#### CONNEXT™ Quick Change Handles

Clear, molded acetate GRIPS are shockproof, shatter-proof and fluted to fit any hand. Including NEW Ratcheting Handle!









CONNEXT3 Ratcheting Handle

#### 1/4 in. Hex Shank Phillips Power Bits and Standard Bits







MBH14

#### Quick Change Hex Adapter

Accepts 1/4 in. hex power bits. Installs into chuck of a standard 3/8 in. power drill. Hex power bits can then be inserted or removed instantly without a key, by retracting the adapter sleeve. Tempered steel. Black finish.



#### Power Bit Extensions

Ball Bearing Lock Big 6 and 10 in. lengths

Accepts 1/4 in. hex power bits. Ball Bearing on holder provides a positive lock on 1/4 in. hex shank power bits. Tempered steel.

BHE<sub>10</sub>

#### **Specifications**

#### 1/4 in. Hex Shank Power Bits

Catalog			Shank Dia.	O/A Lgth.	- 1
Number	Description	Point Size	in.	in.	_
MBLP2	Hex Shank Power Bit	3	1/4	1-15/16	_
MBLP3	Hex Shank Power Bit	2	1/4	1-15/16	_
MBLP4	Hex Shank Power Bit	2	1/4	2-3/4	_
MBSP2	Hex Shank Short Bit	2	1/4	1	i

#### 1/4 in. Hex Shank Insert Bits Holder

Catalog		Hex Opening	Shank Dia.	Nose Dia.	O/A Lgth.	
Number	Description	in.	in.	in.	in.	
MBH14	Bit Holder	1/4	1/4	7/16	3	

#### **Power Bit Extensions**

Catalog		Hex Opening	Shank Dia.	Nose Dia.	O/A Lgth.	
Number	Description	in.	in.	in.	in.	
BHE6	Power Bit Extension	1/4	1/4	9/16	6	
BHE10	Power Rit Extension	1/4	1/4	9/16	10	

#### **Quick Change Hex Adapter**

j	Catalog		Hex Opening	Shank Dia.	Bore Depth	Sleeve Dia.	O/A Length
i	Number	Description	in.	in.	in.	in.	in.
1	HAD1	Hex Adapter	1/4	3/8	7/8	7/8	1-3/4





#### **CONNEXT™ Quick-Change Handles**

Catalog	_	Grip Dia.	Grip Lgth.	Holder Opening	Holder Dia.	Holder Lgth.	O/A Lgth.
Number	Description	in. (mm)	in.	in.	in. (mm)	in. (mm)	in. (cm)
CONNEXT1	Connext1™ Quick-Change Standard Handle	1-1/8 (29)	4-1/8" (105)	1/4	11/16 (18)	1-1/8 (29)	5-1/4 (133)
CONNEXT2	Connext2™ Quick-Change Stubby Handle	1-1/8 (29)	1-7/8" (48)	1/4	11/16 (18)	1-1/8 (29)	3-1/8 (79)



<b>CONNEXT</b> <sup>T</sup>	' Quick-Change Rate	cheting Handle		, t					
Catalog				Grip Dia.	Grip Length	Holder I.D.	Holder O.D.	Holder Length	O/A Length
Number	Description	Driving Positions	Torque Capacity	in. (mm)	in. (mm)	in.	in. (mm)	in. (mm)	in. (mm)
CONNEXT3	Ratcheting Style Handle Long	Forward, Reverse, Locked	Comp. 1/2 solid shaft	1-1/8 (29)	4-1/8 (105)	1/4 Hex	5/8 (16)	1-5/8 (41)	6-3/8" (162)

#### Hex Chuck and Hollow Nut Driver: Size Recognition Color Key



Red - 1/4 in. Hex Opening



Yellow - 5/16 in. Hex Opening





Blue - 3/8" in. Hex Opening Brown - 7/16 in. Hex Opening



#### **CONNEXT™** Hollow Nut Drivers

Catalog		Color	Hex Opening	Hollow Depth	Insert Dia.	Nose Dia.	Holder Dia.	Shaft Total	O/A Lgth.	Shaft
Number	Description	Coded	in.	in. (mm)	in. (mm)	in. (mm)	in. (mm)	Lgth. in. (mm)	in. (cm)	Replacement #
CHD1	Connext™ Hollow Nut Driver	•	1/4	1-1/2 (38)	1/4 (6)	7/16 (11)	11/16 (18)	3-3/8 (86)	7-1/2 (19)	HD1
CHD2	Connext™ Hollow Nut Driver	•	1/4	3 (76)	1/4 (6)	7/16 (11)	11/16 (18)	6-7/8 (175)	10-1/2 (27)	HD2
CHD3	Connext™ Hollow Nut Driver	0	5/16	1-1/2 (38)	1/4 (6)	1/2 (13)	11/16 (18)	3-3/8 (86)	7-1/2 (19)	HD3
CHD4	Connext™ Hollow Nut Driver	0	5/16	3 (76)	1/4 (6)	1/2 (13)	11/16 (18)	6-7/8 (175)	10-1/2 (27)	HD4
CHD5	Connext™ Hollow Nut Driver	•	3/8	1-1/2 (38)	1/4 (6)	9/16 (14)	11/16 (18)	3-3/8 (86)	7-1/2 (19)	HD5
CHD6	Connext™ Hollow Nut Driver	•	3/8	3 (76)	1/4 (6)	9/16 (14)	11/16 (18)	6-7/8 (175)	10-1/2 (27)	HD6



#### **CONNEXT™ Magnetic Long Hand Drivers**

Catalog		Color		Hex Opening	Insert Dia.	Nose Dia.	Holder Dia.	Shaft Total	O/A Lgth.	Shaft
Number	Description	Coded	Reaction	in.	in. (mm)	in. (mm)	in. (mm)	Lgth. in. (mm)	in. (cm)	Replacement #
HHD1	Connext™ Long Hand Driver	•	Magnetic	1/4	1/4 (6)	7/16 (11)	11/16 (18)	6-7/8 (175)	10-1/2 (27)	MSHXL14
HHD2	Connext™ Long Hand Driver	0	Magnetic	5/16	1/4 (6)	1/2 (13)	11/16 (18)	6-7/8 (175)	10-1/2 (27)	MSHXL516
HHD3	Connext™ Long Hand Driver	•	Magnetic	3/8	1/4 (6)	9/16 (14)	11/16 (18)	6-7/8 (175)	10-1/2 (27)	MSHXL38

continued on next page





CONNEXT™ Magnetic Standard Length Hand Drivers										
Catalog		Color	Hex Opening	Hollow Depth	Insert Dia.	Nose Dia.	Holder Dia.	Shaft Total	O/A Lgth.	Shaft
Number	Description	Coded	in.	in. (mm)	in. (mm)	in. (mm)	in. (mm)	Lgth. in. (mm)	in. (cm)	Replacement #
HHD1S	Connext™ Standard Lgth. Hand Driver		Magnetic	1/4 in.	1/4 in. (6)	7/16 in. (11)	11/16 in. (18)	3 in. (76)	7-1/8 in. (18)	MSHL14
HHD2S	Connext™ Standard Lgth. Hand Driver		Magnetic	5/16 in.	1/4 in. (6)	1/2 in. (13)	11/16 in. (18)	3 in. (76)	7-1/8 in. (18)	MSHL516
HHD3S	Connext™ Standard Lgth. Hand Driver	•	Magnetic	3/8 in.	1/4 in. (6)	9/16 in. (14)	11/16 in. (18)	3 in. (76)	7-1/8 in. (18)	MSHL38

#### Magnetic

#### **CONNEXT™ Magnetic Stubby Hand Drivers**



Catalog		Color	Hex Opening	Hollow Depth	Insert Dia.	Nose Dia.	Holder Dia.	Shaft Total	O/A Lgth.	Shaft
Number	Description	Coded	in.	in. (mm)	in. (mm)	in. (mm)	in. (mm)	Lgth. in. (mm)	in. (cm)	Replacement #
HHD1T	Connext™ Stubby Hand Driver	•	Magnetic	1/4 in.	1/4 in. (6)	7/16 in. (11)	11/16 in. (18)	2-1/4 in. (57)	4-1/8 in. (10)	MSH14
HHD2T	Connext™ Stubby Hand Driver	<u> </u>	Magnetic	5/16 in.	1/4 in. (6)	1/2 in. (13)	11/16 in. (18)	2-1/4 in. (57)	4-1/8 in. (10)	MSH516
HHD3T	Connext™ Stubby Hand Driver	•	Magnetic	3/8 in	1/4 in (6)	9/16 in (14)	11/16 in (18)	2-1/4 in (57)	4-1/8 in (10)	MSH38

#### Magnetic

#### CONNEXT™ Short Magnetic Hex Chuck Drivers



Catalog Color	Hex Opening	Insert Dia.	Nose Dia.	O/A Lgth.
Number Coded	in.	in. (mm)	in. (mm)	in. (cm)
MSH14 ●	1/4"	1/4" (6)	7/16" (11)	1-3/4" (44)
MSH14T (Bulk Tub of 100)	1/4"	1/4" (6)	7/16" (11)	1-3/4" (44)
MSH516 •	5/16"	1/4" (6)	1/2" (13)	1-3/4" (44)
MSH516T (Bulk Tub of 100)	5/16"	1/4" (6)	1/2" (13)	1-3/4" (44)
MSH38	3/8"	1/4" (6)	9/16" (14)	1-3/4" (44)

#### Magnetic

## CONNEXT™ Long Magnetic Hex Chuck Drivers



Catalog	Color	Hex Opening	Insert Dia.	Nose Dia.	O/A Lgth.
Number	Coded	in.	in. (mm)	in. (mm)	in. (cm)
MSHL14	•	1/4 in.	1/4 in. (6)	7/16 in. (11)	2-9/16 in. (65)
MSHL14	T (Bulk Tub of 50)	1/4 in.	1/4 in. (6)	7/16 in. (11)	2-9/16 in. (65)
MSHL51	6	5/16 in.	1/4 in. (6)	1/2 in. (13)	2-9/16 in. (65)
MSHL51	6T (Bulk Tub of 50)	5/16 in.	1/4 in. (6)	1/2 in. (13)	2-9/16 in. (65)
MSHL38	•	3/8 in.	1/4 in. (6)	9/16 in. (14)	2-9/16 in. (65)
MSHI 71	6	7/16 in	1/4 in (6)	11/16 in (18)	2-9/16 in (65)

#### Magnetic

#### **CONNEXT™ Extra Long Magnetic Hex Chuck Drivers**



		ALC: NO.				
Catalog			Hex Opening	Insert Dia.	Nose Dia.	O/A Lgth.
Number	Coded		in.	in. (mm)	in. (mm)	in. (cm)
MSHML*	14		1/4 in.	1/4 in. (6)	7/16 in. (11)	4 in. (102)
MSHXL1	4		1/4 in.	1/4 in. (6)	7/16 in. (11)	6 in. (152)
MSHXL1	4T (Bulk Box of 50)		1/4 in.	1/4 in. (6)	7/16 in. (11)	6 in. (152)
MSML51	6 🔾		5/16 in.	1/4 in. (6)	1/2 in. (13)	4 in. (102)
MSHXL5	16 🔍		5/16 in.	1/4 in. (6)	1/2 in. (13)	6 in. (152)
MSHXL5	16T (Bulk Box of 50)		5/16 in.	1/4 in. (6)	1/2 in. (13)	6 in. (152)
MSHXL3	8 •		3/8 in.	1/4 in. (6)	9/16 in. (14)	6 in. (152)

#### **CONNEXT™ Hollow Hex Chuck Drivers**



Catalog	Color		Hex Opening	Hollow Depth	Insert Dia.	Nose Dia.
Number	Coded		in.	in. (mm)	in. (mm)	in. (mm)
HD1	•	1/4 in.	1-1/2 in. (38)	1/4 in. (6)	7/16 in. (11)	3 in. (76)
HD2	•	1/4 in.	3 in. (76)	1/4 in. (6)	7/16 in. (11)	6 in. (152)
HD3	<u> </u>	5/16 in.	1-1/2 in. (38)	1/4 in. (6)	1/2 in. (13)	3 in. (76)
HD4	<u> </u>	5/16 in.	3 in. (76)	1/4 in. (6)	1/2 in. (13)	6 in. (152)
HD5	•	3/8 in.	1-1/2 in. (38)	1/4 in. (6)	9/16 in. (14)	3 in. (76)
HD6	•	3/8 in.	3 in. (76)	1/4 in. (6)	9/16 in. (14)	6 in. (152)

## 6 in 1 Reversible Driver

## & Screwdrivers

### 2 combination bits and 2 hex barrel openings drive 6 different head styles / sizes.

Bit shank firmly locks into handle barrel. Driver bits are individually protected with black oxide. Barrel is chrome plated to protect against rust.



#### **Specifications**

6 in 1 Reversible Driver

Catalog

Number Description

RD6 Driver with 2 combination bits and 2 hex barrel openings