

MODEL RH PINSPOTTER

ROLLING HEAD ITEM #18011

RH MACH II

Duro Dyne, the leader in Insulation Fastening for over half a century offers the very latest in pinspotting technology with the Model RH Mach IIa Rolling Head. Our engineers utilized the best of current technology to provide greater power and reliability for insulation fastening. Trouble-free service and proven solid-state components located for easy access assure high levels of efficiency. The ability to move the trolley instead of the ductwork minimizes material handling. This feature coupled with utilization of welded pins will insure your shop of a cost efficient, quality product.

FEATURES:

TROUBLE-FREE MOVEMENT

Precision polished and hardened tracks combined with ground bearings, assure trouble-free movement of the trolley assembly.

SOLID-STATE COMPONENTS

Components proven under rigorous shop usage, control the pneumatic and weld circuitry. Few adjustments are required.

CONVENIENTLY LOCATED CONTROLS

One knob adjustment sets the weld and dwell times for perfect welds every time. A digital display provides easy reference to the settings for repeatability.

WELD CYCLE INDICATOR

A centrally located weld cycle indicator confirms power to the transformers on every cycle.

OPERATIONS DISPLAY

Your RH Mach IIa Pinspotter is provided with an Operations Display to help identify the source of the problem should your pinspotter fail to perform properly. Watching these lights will give you a clear indication of the electrical flow of the various circuits and components during use. Should a problem arise, you simply press the footswitch and watch to see which light fails to illuminate.

CONTROL REDUNDANCY

The RH Mach IIa features two electronic weld relays. Should one fail during a job a simple flip of a switch puts the backup online so you can continue working while waiting for a replacement part.

ELECTRONIC FEED TRACK SENSOR

An electronic sensor controls the vibrator to assure a full feed track of pins at the ready for welding. Reloading is as easy as positioning the trolley assembly at the front of the machine.



MACHINERY DIVISION
© 2014 Duro Dyne Corporation
Printed in USA 04/2014
BC018403

**DURO
DYNE**®

FEATURES

18 GAUGE CAPACITY

With a custom designed high powered transformer, the RH will weld 2 inch pins to 18 gauge effortlessly.

FIVE FOOT THROAT

The 60" throat allows the placement of pins 1.5" from each end of a 5' sheet without moving the metal. To convert the RH for fittings, draw the welding tip to open end of frame and slide the quick release pin into position locking the weld tip over the fittings mandrill.

PNEUMATIC BRAKE

A pneumatic brake cylinder locks the rolling assembly in position during weld cycle to ensure a quality weld.

PROTECTIVE HARNESS

A specially designed flexible harness protects the air line and weld cable from incidental damage and assures fatigue-free movement.

FOOTSWITCH

The footswitch frees the operator for handling of small fittings and odd shapes. It features a protective covering to minimize the accidental actuation of the machine.



OPTIONS

Roller feed tables adjoining the RH enable work to be easily positioned by the operator; in many cases with just one hand. Productivity is increased and worker fatigue minimized.



SPECIFICATIONS

ELECTRICAL:

Input voltage: 230V, single phase, 60 amp service.

AIR REQUIREMENTS:

Input pressure of 80 psi.

THROAT SIZE:

A 69" throat allows fasteners to be placed up to 1.5" from edge of work without repositioning.

RIB PIN CAPACITY:

The vibrator bowl holds approximately 1,000, 1 inch fasteners. Fasteners of .5" to 1.5" in length may be fed automatically.



The RH MACH IIa utilizes Rib Pin™ fasteners which are resistance welded to ductwork securely attaching the fiberglass insulation. Rib Pins are unsurpassed in holding power. In tests conducted by an independent laboratory, samples exhibited holding strength averaging three times that of nail type fasteners.

Note: For best performance, use genuine Duro Dyne insulation fasteners

Item#	Rib Pin	Approx Clip Size	For Liner Size	Pkg.
26023	CP-12	1/2"	1/2"	1M
26028	CPB-12	1/2"	1/2"	5M
26024	CP-34	3/4"	1"	1M
26029	CPB-34	3/4"	1"	5M
26025	CP-100	1"	1" Heavy Density	1M
26030	CPB-100	1"	1" Heavy Density	5M
26026	CP-150	1 1/2"	1 1/2"	1M
26031	CPB-150	1 1/2"	1 1/2"	3M
26027	CP-200	2"	2"	1M
26038	CPB-200	2"	2"	3M



Certified to ISO 9001:2008



Duro Dyne East Division, Bay Shore, NY

Duro Dyne Midwest Division, Fairfield, OH

Duro Dyne West Division, Santa Fe Springs, CA

Duro Dyne Canada, Lachine, Quebec, Canada

631-249-9000

513-870-6000

562-926-1774

514-422-9760

Fax: 631-249-8346

Fax: 513-870-6005

Fax: 562-926-5778

Fax: 514-636-0328

www.durodyne.com E-mail: durodyne@durodyne.com